


Application Method & pH**Risk Information****Safety Information****Quality Certificates****Application Areas**

SBC- Coolclean

Dirt and Oil Cleaner for Coolers

Features

A powerful oil and tar solvent that can emulsify with water is a special and safe product. It does not contain acid or alkali. It is a mixture of non-flammable solvents. Coolclean creates a viscous emulsion when mixed with water thanks to its special formula. In this form, it adheres to vertical surfaces and cleans stubborn dirt, oil, and residue. It does not leave the surface it adheres to until the oil and tar dissolve. It is not flammable. Therefore, it is safer than other solvents, diesel and gasoline. It does not produce toxic or irritating smoke. It is economical, does not flow or drip as it can adhere to surfaces, and there is no product loss. It is mixed with 4 to 8 units of water in a ratio of 1 to 1. It reduces cleaning costs, does not require scrubbing, and reduces labor.

Composition: Contains chlorinated solvents and emulsifying surface active agents. ,

pH (10% solution): 7 ± 1.0

Specific gravity g/cm³: 1.35 ± 0.1

Areas of Use

Used in the cooler cleaning of diesel machines, fuel oil heaters. It is used in the exhaust side of turbo blowers, and the flame side cleaning of steam boilers. It removes organic and inorganic dirt and oils from work machines, car engine blocks and all kinds of equipment. It gives much better results than cleaning with steam, diesel and detergent in car engine blocks. It is used in the cleaning of tank surfaces.

Usage Method

After diluting one unit of Coolclean with the same amount of water, shake for 1 minute. 2 - 3 times more water can be added. Spray on the surface, wait 5 - 10 minutes and rinse with pressurized clean water. It is possible to use it pure and rinse with clean water.

NOTE: Adequate ventilation should be provided during the use process. Do not breathe!

Storage

Do not store below 2 °C (35.6 °F) and above 50 °C (122 °F). Shelf life is 4 years from the date of production.

Packaging

20 liters

Product code: TC 81027